## **Q40 Temporary Hoarding & Gates Specification**

To be read in conjunction with Preliminaries/General conditions

Description: On-ground or in-ground temporary perimeter hoarding system

Standard: BS1722-14: 2017

TWf2012: 01, August 2020 BS EN ISO 1461: 2009

Manufacturer: Panthera Group Ltd info@pantheragroup.com

Tel. 0845 165 1234 www.pantheragroup.com

Product Reference: EnviroHoard™ SHIELD - On/In Ground Net Zero Temporary Hoarding

System

Panel type: 100% recycled uPVC or Virgin uPVC

Support options: 800kg EnviroBlok

Panel width: 500mm

Panel depth: 35mm

Available heights

Select as required: 3.0m solid uPVC panel

2.4m solid uPVC panel with 0.6m white twin wire mesh

Finish: White 100% recycled (recycled product colour shades may differ)

Choice of RAL colours if virgin uPVC

Panel installation: Bottom of panel maximum 50mm above ground.

Fixed to steel rails using electro galvanised steel clips

Security topping Anti-climb aluminium rollers

options: White upvc tumblers (single or double row)

EnviroHoard E-Pulse electric fence

SHS Posts: Hot dip galvanised to BS EN ISO 1461: 2009

Post dimensions: Main post 2220x80x40mm

Extension post 1220x80x40mm

Maximum post

Centres: Dependant on site specific design

Fixings: M16/M12 with nylock nuts for frame.

Electro galvanised steel clips for panels

Support: Installation using EnviroHoard™ 4-way adjustable bracket fixed to

800kg low carbon EnviroBlok

\*Support to be confirmed by the temporary works engineer

Security Level: Medium/High

Vehicle Gate: Compatible with full range of EnviroHoard™ vehicle gates

Pedestrian Gate: Compatible with EnviroHoard™ single and double pedestrian gates

Sustainability: System has undergone cradle to grave Life Cycle Assessment (LCA) in

accordance with European wide standard EN 15804:2019

Warranty: 10 years against manufacturing defects

Notes: All dimensions are nominal, for further information please contact Panthera

Group

Information is correct at time of publishing. As part of our policy of continuous improvement, we reserve the right to modify product

specification without notice